

BITUMEN PRIMER TECHNICAL DATA SHEET

- Seals Roofing Decks Against Moisture
- Increases Adhesion For Roofing Membranes
- Covers Up To 12m² Per Litre (Dependant On Porosity Of Surfaces)

DESCRIPTION:

Tuskbond Bitumen Roofing Primer is a solvent based, cold applied bituminous primer. Designed to seal roofing decks and increase adhesion potential prior to application of membranes or vapour control layers. Tuskbond Bitumen Roofing Primer can be easily spread using a brush or roller, covering the surface quickly.

TECHNICAL SPECIFICATION:

PROPERTY TUSKBOND BITUMEN PRIMER

Colour Black

Size 5L Berg Container

Coverage:

Metal6-12m² per litreConcrete6-8m² per litreLightweight Screeds3.5-5m² per litre

Viscosity @ 20°C 50-100cps
Specific Gravity 0.89
Solids Content 40%
Flash Point 38°C

Drying Time Touch dry after 30-60 minutes.

3-6 hours depending on conditions

STORAGE & SHELF LIFE:

Protect from extremes of temperature in a controlled environment, and away from direct sunlight or heat sources. DO NOT ALLOW THE PRODUCT TO FREEZE. Stored under the correct conditions, in original, unopened containers, the product will have a shelf life of 12 months.





TUSKBOND Roofing Solutions

BITUMEN PRIMER TECHNICAL DATA SHEET

DIRECTIONS FOR USE:

- Surfaces should be clean and free from grease, dirt or dust.
- Ideally, surfaces should be dry but the material can be applied to damp (not wet) surfaces.
- Apply evenly across the surface using a brush or roller in one full coating.
- To comply with BS Code of Practice 144:
 Part 3: Clause 4.6.1 all solvent must be allowed to evaporate from the primer. It is recommended that a safe drying margin of 2 hours is allowed.

DISCLAIMER:

All the information in the Data Sheet is based on practical experience and is published in good faith. However, because we have no control over the manner or conditions in which our products are used, or over work undertaken or end product manufactured by the purchaser, we cannot accept liability for results. Responsibility for ascertaining the suitability of products for purpose rests with the purchaser. All conditions, representations, statements, warranties or guarantees whatsoever, whether express, implied or statutory, in respect of any goods manufactured, sold or supplied by us are hereby expressly excluded and we accept no liability in respect of any claim for damage or consequential loss caused to any property arising directly or indirectly out of the use of our products or goods.

