

Printing date 12.03.2020 Version number 3 Revision: 12.03.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: illbruck FM365

· MSDS code: A-I-FM365

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture Sealant

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

tremco illbruck Productie B.V. Vlietskade 1032, 4241 WC Arkel

T: +31 (0) 183568000, F: +31 (0) 183568100

msds@tremco-illbruck.com

· Further information obtainable from:

tremco illbruck Ltd

Coupland Road, Hindley Green, Wigan, WN2 4HT

T: +44 (0) 1942251400, F: +44 (0) 1942251410

www.tremco-illbruck.co.uk, uk.info@tremco-illbruck.com

· 1.4 Emergency telephone number:

During office hours tel.: +31 (0) 183568019. At all other times please contact your national poisoning centre.

During office hours tel.: +44 (0) 1942251400. At all other times it is recommended to call NHS 111 (England/Wales/Scotland), 01 809 2166 (ROI), or otherwise to contact a doctor.

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

Aerosol 1	H222-H229	Extremely flammable aerosol. Pressurised container: May burst if heated.
Acute Tox. 4	H332	Harmful if inhaled.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
Resp. Sens. 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Sens. 1	H317	May cause an allergic skin reaction.
Carc. 2	H351	Suspected of causing cancer.
Lact.	H362	May cause harm to breast-fed children.
STOT SE 3	H335	May cause respiratory irritation.
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure. (Contd. on page 2)

GB



Printing date 12.03.2020 Version number 3 Revision: 12.03.2020

Trade name: illbruck FM365

(Contd. of page 1)

Aquatic Chronic 4 H413 May cause long lasting harmful effects to aquatic life.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02 GHS07 GHS08

- · Signal word Danger
- · Contains:

diphenylmethanediisocyanate, isomers and homologues

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H362 May cause harm to breast-fed children.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H413 May cause long lasting harmful effects to aquatic life.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P284 In case of inadequate ventilation wear respiratory protection.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

· Supplemental information:

EUH204 Contains isocyanates. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.

- GB

(Contd. on page 3)



Printing date 12.03.2020 Version number 3 Revision: 12.03.2020

Trade name: illbruck FM365

(Contd. of page 2)

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Active substance with propellant

· Dangerous components:		
CAS: 9016-87-9	diphenylmethanediisocyanate, isomers and homologues Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	30-<50%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane Flam. Gas 1, H220; Press. Gas (Comp.), H280	10-<20%
CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether Flam. Gas 1, H220; Press. Gas (Comp.), H280	10-<20%
CAS: 85535-85-9 EINECS: 287-477-0 Reg.nr.: 01-2119519269-33-xxxx	alkanes, C14-17, chloro Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Lact., H362	5-<10%
CAS: 9082-00-2	Ethoxylated/propoxylated glycerol Acute Tox. 4, H302	5-<10%
CAS: 25791-96-2 NLP: 500-044-5	Glycerol, propoxylated Acute Tox. 4, H302	5-<10%
EC number: 807-935-0 Reg.nr.: 01-2119486772-26-xxxx	tris(2-chloro-1-methylethyl)phosphate Acute Tox. 4, H302	1-<5%

· SVHC -

· Additional information:

For the wording of the listed hazard phrases refer to section 16.

While curing the following substances are formed and released by a reaction with atmospheric humidity: Carbon dioxide (CO2)

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Take affected persons out of danger area and lay down.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If symptoms persist consult doctor.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** Do not induce vomiting; call for medical help immediately.

(Contd. on page 4)



Printing date 12.03.2020 Version number 3 Revision: 12.03.2020

Trade name: illbruck FM365

(Contd. of page 3)

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

- · Information for doctor: No further relevant information available.
- · Hazards No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

Carbon monoxide (CO)

Carbon dioxide (CO2)

Nitrogen oxides (NOx)

Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:

Hydrogen cyanide (HCN)

- 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Dispose of contaminated material as waste according to Section 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

(Contd. on page 5)



Printing date 12.03.2020 Version number 3 Revision: 12.03.2020

Trade name: illbruck FM365

(Contd. of page 4)

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- Information about storage in one common storage facility: Store away from water.
- Further information about storage conditions:

Keep container tightly sealed.

Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:				
CAS:	CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues			
WEL	Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³ Sen; as -NCO			
CAS: 115-10-6 dimethyl ether				
WEL	Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm			

· DNELs

· Long term effects			
CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues			
Inhalative	industrial	0.05 mg/m3 (workers) (systemic and local effects)	
	consumer	0.025 mg/m3 (general public) (systemic and local effects)	
CAS: 115-	10-6 dimet	thyl ether	
Inhalative	industrial	1,894 mg/m3 (workers) (systemic effects)	
	consumer	471 mg/m3 (general public) (systemic effects)	
tris(2-chlo	tris(2-chloro-1-methylethyl)phosphate		
Oral	consumer	0.52 mg/kg/24h (general public) (systemic effects)	
Dermal	industrial	2.08 mg/kg/24h (workers) (systemic effects)	
	consumer	1.04 mg/kg/24h (general public) (systemic effects)	
Inhalative	industrial	5.82 mg/m3 (workers) (systemic effects)	
	consumer	1.46 mg/m3 (general public) (systemic effects)	
		(Co	ntd. on page 6)

– GB



Printing date 12.03.2020 Version number 3 Revision: 12.03.2020

Trade name: illbruck FM365

			(Contd. of page 5
Short terr	n effects		
CAS: 901	6-87-9 diph	enylmethanediisocyanate, isomers and homologues	
Oral	consumer	20 mg/kg/24h (consumers) (systemic effects)	
Dermal	industrial	50 mg/kg/24h (workers) (systemic and local effects)	
	consumer	25 mg/kg/24h (consumers) (systemic effects)	
Inhalative	industrial	0.1 mg/m3 (workers) (systemic and local effects)	
	consumer	0.05 mg/m3 (general public) (local effects)	
tris(2-chlo	oro-1-meth	ylethyl)phosphate	
Dermal	industrial	8 mg/kg/24h (workers) (systemic effects)	
	consumer	4 mg/kg/24h (general public) (systemic effects)	
Inhalative	industrial	22.4 mg/m3 (workers) (systemic effects)	
	consumer	11.2 mg/m3 (general public) (systemic effects)	
PNECs			
CAS: 901	6-87-9 diph	enylmethanediisocyanate, isomers and homologues	
PNEC 1 r	ng/L (fresh	water)	
10	mg/L (inter	mittent release)	
0.1	l mg/L (salt	water)	
CAS: 115	-10-6 dimet	hyl ether	
PNEC 0.1	155 mg/L (fr	esh water)	
16	0 mg/L (sev	vage treatment plant)	
1.5	549 mg/L (ir	ntermittent release)	
0.0)16 mg/L (s	alt water)	
PNEC 0.0)45 mg/kg (soil)	
0.069 mg/kg (sediment (salt water))			
tris(2-chloro-1-methylethyl)phosphate			
PNEC 0.6	64 mg/L (fre	sh water)	
0.0)64 mg/L (n	narine)	
PNEC 1.7	mg/kg dwt	(soil)	
1.3	34 mg/kg dv	vt (sediment (salt water))	
		on: The lists valid during the making were used as basis	

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Do not inhale gases / fumes / aerosols.

(Contd. on page 7)



Printing date 12.03.2020 Version number 3 Revision: 12.03.2020

Trade name: illbruck FM365

(Contd. of page 6)

· Respiratory protection:

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

For further guidance,

please refer to HSE HSG53 "Respiratory Protective Equipment at work - A Practical Guide".

Protection of hands:



Protective gloves

Material of gloves

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.7 mm

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

· Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6).

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles

· Body protection:



Protective work clothing

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Aerosol

Colour: According to product specification

Odour: CharacteristicOdour threshold: Not determined.

· pH-value: Not determined.

· Melting point/freezing point: Not applicable, as aerosol.

Undetermined.

(Contd. on page 8)



Printing date 12.03.2020 Version number 3 Revision: 12.03.2020

Trade name: illbruck FM365

	(Contd. of page 7)	
· Initial boiling point and boiling range: Not applicable, as aerosol.		
· Flash point:	-97 °C	
· Flammability (solid, gas):	Not applicable.	
· Decomposition temperature:	Not determined.	
· Auto-ignition temperature:	Product is not selfigniting.	
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.	
· Explosion limits: Lower: Upper:	3.0 Vol % 18.6 Vol %	
· Vapour pressure at 20 °C:	5200 hPa	
 Density at 20 °C: Relative density Vapour density Evaporation rate 	1 g/cm³ Not determined. Not determined. Not applicable.	
· Solubility in / Miscibility with water:	Immiscible / difficult to mix.	
Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.	
· Solvent content: VOC (EU) VOC (EC) · 9.2 Other information	228.5 g/l 20.40 % No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

GB



Printing date 12.03.2020 Version number 3 Revision: 12.03.2020

Trade name: illbruck FM365

(Contd. of page 8)

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity

Harmful if inhaled.

· LD/LC50 values relevant for classification:				
CAS: 9016	CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues			
Oral	LD50	>10,000 mg/kg (rat)		
Dermal	LD50	>10,000 mg/kg (rabbit)		
Inhalative	LC50/4 h	1.5 mg/L (rat)		
CAS: 9082	CAS: 9082-00-2 Ethoxylated/propoxylated glycerol			
Oral	LD50	>500 mg/kg (rat)		
Dermal	LD50	>2,000 mg/kg (rabbit)		
CAS: 2579	CAS: 25791-96-2 Glycerol, propoxylated			
Oral	LD50	1,999 mg/kg (rat)		
tris(2-chloro-1-methylethyl)phosphate				
Oral	LD50	632 mg/kg (rat)		

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity

Suspected of causing cancer.

· Reproductive toxicity

May cause harm to breast-fed children.

STOT-single exposure

May cause respiratory irritation.

- STOT-repeated exposure
- May cause damage to organs through prolonged or repeated exposure.
- · Aspiration hazard Based on available data, the classification criteria are not met.

GB

(Contd. on page 10)



Printing date 12.03.2020 Version number 3 Revision: 12.03.2020

Trade name: illbruck FM365

(Contd. of page 9)

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic to	· Aquatic toxicity:				
CAS: 9016	CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues				
LC0/96 h	>1,000 mg/L (brachydanio rerio)				
EC50/24 h	>1,000 mg/L (daphnia magna)				
CAS: 9082	CAS: 9082-00-2 Ethoxylated/propoxylated glycerol				
LC50/48 h	>100 mg/L (brachydanio rerio)				
EC50/48 h	>100 mg/L (daphnia magna)				
EC50/72 h	>1,000 mg/L (scenedesmus capricornutum)				
tris(2-chlor	tris(2-chloro-1-methylethyl)phosphate				
LC50/96 h	51 mg/L (pimephales promelas)				

- · 12.2 Persistence and degradability No further relevant information available.
- · Other information: The product is not easily biodegradable.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.

· Ecotoxical effects:

CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues

NOEC/21 d >10 mg/L (daphnia magna)

· Remark:

Using the aforementioned tests, it can be proven that the ecotoxicological effects are very low. In keeping with the underlying regulations, the labelling was adjusted accordingly.

Other information:

This product contains no substances in Annex I to Directive EC 1005/2009 concerning ozone depleting substances

- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · **vPvB**: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 11)



Printing date 12.03.2020 Version number 3 Revision: 12.03.2020

Trade name: illbruck FM365

	(Contd. of page 10)			
· European waste catalogue				
16 05 04*	gases in pressure containers (including halons) containing hazardous substances			
08 05 01*	waste isocyanates			
HP3	Flammable			
HP4	Irritant - skin irritation and eye damage			
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity			
HP7	Carcinogenic			
HP13	Sensitising			
HP14	Ecotoxic			

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number	
· ADR, IMDG, IATA	UN1950

· 14.2 UN proper shipping name

ADR 1950 AEROSOLS 1950 AEROSOLS

· IMDG AEROSOLS (alkanes, C14-17, chloro), MARINE

POLLUTANT

· IATA AEROSOLS, flammable

· 14.3 Transport hazard class(es)

· ADR



· Class 2 5F Gases.

· Label 2.1

· IMDG



· Class 2.1

(Contd. on page 12)



Printing date 12.03.2020 Version number 3 Revision: 12.03.2020

Trade name: illbruck FM365 (Contd. of page 11) · Label 2.1 ·IATA 2.1 · Class · Label 2.1 · 14.4 Packing group · ADR, IMDG, IATA Void · 14.5 Environmental hazards: Product contains environmentally hazardous substances: alkanes, C14-17, chloro · Marine pollutant: Yes Symbol (fish and tree) · 14.6 Special precautions for user Warning: Gases. · Hazard identification number (Kemler code): · EMS Number: F-D.S-U Stowage Code SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. Segregation Code SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. Transport/Additional information: · ADR Limited quantities (LQ) 1L Excepted quantities (EQ) Code: E0 Not permitted as Excepted Quantity Transport category 2 Tunnel restriction code D

(Contd. on page 13)



Printing date 12.03.2020 Version number 3 Revision: 12.03.2020

Trade name: illbruck FM365

(Contd. of page 12)

·IMDG

· Limited quantities (LQ)

Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

· UN "Model Regulation": UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

• **15.1 Safety**, health and environmental regulations/legislation specific for the substance or mixture "CLP" Regulation (EC) No 1272/2008 (OJ L 353, 31.12.2008, p.1).

1L

"REACH" Regulation (EC) No 1907/2006 (OJ L 396, 30.12.2006, p.1, with subsequent amendments). COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

HSE EH40/2005 Workplace Exposure Limits (as amended)

Guidance on the classification and assessment of waste | Technical Guidance WM3 (1st edition 2015) 2001/118/EC as regards the list of wastes

2008/98/EC on waste

- · Directive 2012/18/EU
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:
- · Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

- Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57 Not applicable.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

(Contd. on page 14)



Printing date 12.03.2020 Version number 3 Revision: 12.03.2020

Trade name: illbruck FM365

(Contd. of page 13)

H351 Suspected of causing cancer.

H362 May cause harm to breast-fed children.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Department issuing SDS:

Prepared and verified in accordance with "REACH" Regulation (EC) No 1907/2006, Annex II, Part A, 0.2.3.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases - Category 1

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Acute Tox. 4: Acute toxicity - inhalation - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity - Category 2

Lact.: Reproductive toxicity – effects on or via lactation

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4

* Data compared to the previous version altered.

GB