TECHNICAL DATA SHEET



15009 PVC Tape

DESCRIPTION

A high quality flame retardant PVC Electrical Tape available in a full range of colours and in lengths 33m, 20m and 10m as standard on a 3"core. PVC tape has High resistance to corrosion, U.V, moisture and chemicals.

Technical Specification.

Type of Film : PVC.

Thickness : 0.13mm

Tensile Strength (Kg/cm) : 2.5

Elongation at Break (Kg/cm) : 200

Adhesion (Kg/cm) : 18

Dielectric Breakdown (Volts) :6,500 Dielectric Strength (Volts/mil) :1,250

Bs EN 60454 Type 2

Note:

All our products are subjected to a strict quality control by our QM-System, which is in accordance with ISO/TS 16949, DIN EN ISO 9001 and DIN EN ISO 14001. The information is based on our present knowledge and our experience. Because of the large number of possible influences during the processing and application of our products, this information does not release the user from the obligation to conduct his own tests and trials. Users of our products are responsible for observing any patent rights that may exist and for following existing regulations. Our applications technology section is always pleased to give advice about suitability tests on original materials.

These suggestions and data are based on information we believe to be reliable and accurate, but no guarantee of their accuracy is made. Industrial Adhesive Solutions Limited shall not be liable for any damage, loss or injury, direct or consequential arising out of the use or the inability to use the product. In every case, we urge and recommend that purchasers, before using any product in full scale production, make their own tests to determine whether the product is of satisfactory quality and suitability for their operations, and the user assumes all risk and liability whatsoever, in connection therewith. Please contact us for further assistance and information.





