

# TECHNICAL DATA SHEET

## 1713 BANNER STIFFENING TAPE

A laminated construction using a siliconised HDPE and high tack acrylic adhesive to produce a self wound liner free tape.

The tape itself will withstand external use and can have a life expectancy in excess of 2 years if correctly used and applied. Fade or discoloration will depend on exposure to and intensity of UV and weather conditions.

### TECHNICAL DATA: Foil only

Materials	200 micron High Density PE foil
Weight	196 gsm
Tensile Strength	MD 4.0 kN/M ASTM D862 TD 4.4 kN/M ASTM D862
Elongation	MD 1400 % ASTM D862 TD 1800% ASTM D862
Opacity	85% ISO 2471

### ADHESIVE CONTENT: High Tack modified acrylic




Coating Weight	100 gsm
Adhesive thickness	100 micron
Adhesive strength ( 24 hour 300mm / min peel)	25N / 25mm
Adhesive temp performance	-40C +160C
Colours	WHITE
Roll Size	width varies to order
Roll length	25M

The values presented in this document have been determined by standard test methods and are average values that should not be used for specification purposes. Our recommendations regarding the use of our products are based on tests considered by INDUSTRIAL ADHESIVE SOLUTIONS LIMITED to be reliable, but the customer must conduct his own tests to determine the suitability of the product to the individuals application and requirements. INDUSTRIAL ADHESIVE SOLUTIONS LIMITED do not accept responsibility or liability, directly or consequentially, for loss or damage caused as a result of our recommendations.

These suggestions and data are based on information we believe to be reliable and accurate, but no guarantee of their accuracy is made. Industrial Adhesive Solutions Limited shall not be liable for any damage, loss or injury, direct or consequential arising out of the use or the inability to use the product. In every case, we urge and recommend that purchasers, before using any product in full scale production, make their own tests to determine whether the product is of satisfactory quality and suitability for their operations, and the user assumes all risk and liability whatsoever, in connection therewith. Please contact us for further assistance and information.



For further information, samples and a demonstration, please contact:

 0121 556 9900  0121 556 9034  enquiry@indasol.co.uk

For our Ireland sales manager please contact us on 07795 151814

**NEXT DAY DELIVERY AVAILABLE** 

**www.indasol.co.uk**