

TECHNICAL DATA SHEET

24213-E – Ultra High Tack Double Sided Tape

Description

Our Ultra High Tack Double Sided Tissue Tape uses a non-woven tissue as carrier, coated with solvent acrylic adhesive on both sides, and protected with white double-sided PE coated silicone release paper. Suitable for general bonding, bag sealing, photos sticking, envelop sealing, shopping bag making, fabric / leather laminating, paper and film flying splicing, fabric positioning during computer embroidering, carpet fixing, foam laminating and die-cutting etc.

Technical Data

Adhesive	: Solvent Acrylic
Total Thickness	: 170 Micron
Adhesion to Steel	: 22 N/25mm
Tack Rolling Ball	: 5cm
Adhesion to Liner	: 0.5 N/25mm
Holding Power	: 300 Min./(25mm x 25mm). 1kg
Service Temperature	: -30 ~ +120°C
Applying Temperature	: +10 ~ 40°C
Shelf Life	: 12 Months




Note:

All our products are subjected to a strict quality control by our QM-System, which is in accordance with ISO/TS 16949, DIN EN ISO 9001 and DIN EN ISO 14001. The information is based on our present knowledge and our experience. Because of the large number of possible influences during the processing and application of our products, this information does not release the user from the obligation to conduct his own tests and trials. Users of our products are responsible for observing any patent rights that may exist and for following existing regulations. Our applications technology section is always pleased to give advice about suitability tests on original materials.

These suggestions and data are based on information we believe to be reliable and accurate, but no guarantee of their accuracy is made. Industrial Adhesive Solutions Limited shall not be liable for any damage, loss or injury, direct or consequential arising out of the use or the inability to use the product. In every case, we urge and recommend that purchasers, before using any product in full scale production, make their own tests to determine whether the product is of satisfactory quality and suitability for their operations, and the user assumes all risk and liability whatsoever, in connection therewith. Please contact us for further assistance and information.



For further information, samples and a demonstration, please contact:

 0121 556 9900  0121 556 9034  enquiry@indasol.co.uk

For our Ireland sales manager please contact us on 07795 151814

NEXT DAY DELIVERY AVAILABLE 

www.indasol.co.uk