

# TECHNICAL DATA SHEET

## 7080AH-2430 POLYETHYLENE FOAM TAPE

### DESCRIPTION:

- Closed cell PE foam, with a paper release liner
- Coated on both sides with a high quality pressure sensitive solvent acrylic adhesive

### APPLICATIONS:

- Mirror Mounting, Sign Fabrication, Mounting plastic profiles and sheet. Point of sales and display, ideal for die-cutting.

### TECHNICAL VALUES:

FOAM THICKNESS	=	1.0mm
FOAM DENSITY	=	70kg / m <sup>3</sup>
FOAM COLOUR	=	WHITE
LINER COLOUR	=	WHITE PAPER
180° PEEL ADHESION TO STAINLESS STEEL	=	27 N/25mm
STATIC SHEAR ADHESION 500 hour loading	=	0.8 Kg/cm <sup>2</sup> .
SERVICE TEMPERATURE	=	- 40°C to +120°C

### FEATURES AND BENEFITS:

- High performance double-sided Polyethylene foam
- Designed for high shear applications with U.V. resistance
- No known hazards with this product
- Performance may vary across the service temperature range
- Good moisture and humidity resistance

### STORAGE DETAILS:

- Life expectancy will vary with temperature and humidity
- Shelf life is one year from date of despatch
- Low temperatures may increase the risk of condensation, which will reduce the tack of the product.

Unless stated otherwise all values given are average. All of the tapes in our range should be thoroughly tested on the substrates in the particular application they are intended for. The customer has to decide on the tapes suitability for the intended application.

These suggestions and data are based on information we believe to be reliable and accurate, but no guarantee of their accuracy is made. Industrial Adhesive Solutions Limited shall not be liable for any damage, loss or injury, direct or consequential arising out of the use or the inability to use the product. In every case, we urge and recommend that purchasers, before using any product in full scale production, make their own tests to determine whether the product is of satisfactory quality and suitability for their operations, and the user assumes all risk and liability whatsoever, in connection therewith. Please contact us for further assistance and information.



For further information, samples and a demonstration, please contact:

 0121 556 9900  0121 556 9034  enquiry@indasol.co.uk

For our Ireland sales manager please contact us on 07795 151814

**NEXT DAY DELIVERY AVAILABLE** 

**www.indasol.co.uk**