

Product Sheet

MASKING TAPE - MTE



MASKING TAPE - MTE

The original crepe paper masking tape

High performance
refinish grade - a
bodyshop essential

Exceptional mechanical performance



80° C temperature
resistance



Natural rubber resin
adhesive



Consistency of thickness

Features and Benefits

Solvent resistant



Paint will not bleed

Excellent adhesion



Good mechanical strength

Flexible



Easy to shape on contours

Easy/clean removal



Leaves no residue

Consistency of thickness



Uniform paint edge

Easy roll release



Easy to apply

80° temp rating



Low bake refinishing

Substrates

Old paint
Fillers
Primers
Top Coats
Clear Coats
Gel Coat
Wood Coatings
Walls and Dry Walls
Painted Surface
Primed Surface
Composite
Plastic

Applications

Automotive masking
Paint and Decorative masking

Product Sheet

MASKING TAPE - MTE

Suited for



Automotive Refinishing



Composite Industries

Technical Specifications

Colour	Ivory	Ivory	Ivory	Ivory	Ivory	Ivory	Ivory	Ivory
Width	12 mm	15 mm	18 mm	24 mm	30 mm	36 mm	48 mm	72 mm
Length	50 m	50 m	50 m	50 m	50 m	50 m	50 m	50 m
Backing	Semi-crepe paper	Semi-crepe paper	Semi-crepe paper	Semi-crepe paper	Semi-crepe paper	Semi-crepe paper	Semi-crepe paper	Semi-crepe paper
Adhesive	Natural rubber	Natural rubber	Natural rubber	Natural rubber	Natural rubber	Natural rubber	Natural rubber	Natural rubber
Thickness	0,135mm	0,135mm	0,135mm	0,135mm	0,135mm	0,135mm	0,135mm	0,135mm
Temperature Resistance	80° - 30 min	80° - 30 min	80° - 30 min	80° - 30 min	80° - 30 min	80° - 30 min	80° - 30 min	80° - 30 min
Removal Time Indoor	5 days	5 days	5 days	5 days	5 days	5 days	5 days	5 days
Elongation at Break	9,5%	9,5%	9,5%	9,5%	9,5%	9,5%	9,5%	9,5%
Adhesion to Steel	270 g/cm	270 g/cm	270 g/cm	270 g/cm	270 g/cm	270 g/cm	270 g/cm	270 g/cm
Rolling Ball Test	1 cm	1 cm	1 cm	1 cm	1 cm	1 cm	1 cm	1 cm
Tensile Strength	4,0 kg/cm	4,0 kg/cm	4,0 kg/cm	4,0 kg/cm	4,0 kg/cm	4,0 kg/cm	4,0 kg/cm	4,0 kg/cm
Package Qty.	72	60	48	36	32	24	20	12