

TECHNICAL DATA SHEET

GUIDELINES FOR CARPET PROTECTION FILM

Please carefully read these application and limitations before using this product.

USAGE

1. Protection against spills, scratches, stains & dirt during building works, remodelling, painting, decoration, furniture removal and parties
2. Heavy duty rip-resistant material.
3. Quick & Simple to apply and remove.
4. Self adhesive for secure positioning.

APPLICATION

1. Before applying the film ensure the surface is clean and dry.
2. **Customers must fully evaluate the product by testing prior to using.** Test the film for 48 hours on a small hidden area of carpet to ensure compatibility with the particular carpet and to ensure that there is no adhesive transfer or damage to carpet.
3. To apply the roll, lay it on the floor facing the direction required to cover. Push the roll forward a small distance and press down firmly to ensure the film has adhered to the carpet. This is for reverse wound rolls. For standard wound, apply as normal film.
4. Continue to unroll, pressing down and smoothing out any air pockets, checking the film is rolled straight.

LIMITATIONS

1. **Do not leave the film on carpet for longer than 4 weeks.**
2. For use on **Synthetic Carpets** Only.
3. Not to be used with underfloor heating.
4. **Do not use on long wool carpet.** Not suitable for use on wool or oriental carpets, rugs, worn carpets or **deep pile Saxony carpets or deep pile polypropylene carpets.** See technical for advise here.
5. **Do not apply on newly laid carpets** where a glue or adhesive has been used. Allow up to 72 hours for any vapours to evaporate before laying the film.
6. **Do not apply on new cleaned carpets.** If the carpet had been recently cleaned, allow it to completely dry for a minimum of 10 days before using the film.
7. **Do not apply to a damp surface,** which will prevent any moisture from evaporating and could cause discoloration of carpet fibers.
8. Film is one time use only. Remove and dispose of in accordance with local environmental regulations.
9. High traffic areas or outdoor exposure may require renewal of film weekly or sooner.
10. The product should be stored no longer than 12 months at room temperature.

These suggestions and data are based on information we believe to be reliable and accurate, but no guarantee of their accuracy is made. AVANTI Tapes Limited shall not be liable for any damage, loss or injury, direct or consequential arising out of the use or the inability to use the product. In every case, we urge and recommend that purchasers, before using any product in full scale production, make their own tests to determine whether the product is of satisfactory quality and suitability for their operations, and the user assumes all risk and liability whatsoever, in connection therewith. Please contact us for further assistance and information.



For further information, samples and a demonstration, please contact:

0121 556 9900 0121 556 9034 sales@protectiontapes.co.uk

For our Ireland sales manager please contact us on 07795 151814

NEXT DAY DELIVERY AVAILABLE

www.protectiontapes.co.uk