

TECHNICAL DATA SHEET

AV253X

Properties	Unit Measure	Values and Characteristics
Item Type		AV253X
Environmental condit temperature	Degree	25 +/- 10%
Relative humidity	%	80 +/- 10%
Backing material		LDPE (with special edition)
Type of adhesive		Water acrylic
Colour		Clear/Blue/Red/Green
Total thickness	microns	50 microns +/- 5 microns
Backing tensile strength (MD)	N/25mm	>16
Backing tensile strength (TD)	N/25mm	>12
Adhesion	N/in	2.5 +/- 0.25
Elongation at break (MD)	%	>280
Elongation at break (TD)	%	>300

AV253X is available in Blue, Clear or Green and is ideal for protection of painted metals, plastic sheets, profiles, hard surfaces and window protection.

We can convert the product from master logs to widths from 15mm to 1500mm and lengths of 25M, 50M, 100M, 250M and 1000M. We can also offer bespoke packaging and in some cases reverse wound products.

These suggestions and data are based on information we believe to be reliable and accurate, but no guarantee of their accuracy is made. AVANTI Tapes Limited shall not be liable for any damage, loss or injury, direct or consequential arising out of the use or the inability to use the product. In every case, we urge and recommend that purchasers, before using any product in full scale production, make their own tests to determine whether the product is of satisfactory quality and suitability for their operations, and the user assumes all risk and liability whatsoever, in connection therewith. Please contact us for further assistance and information.



For further information, samples and a demonstration, please contact:

0121 556 9900  0121 556 9034  sales@protectiontapes.co.uk

For our Ireland sales manager please contact us on 07795 151814

NEXT DAY DELIVERY AVAILABLE 

www.protectiontapes.co.uk