





MASQ DATA SHEET

NB. This technical information and data should be considered representative only, and should not be used for specific purposes.	Interior and Exterior				Interior Only		
	Premier	Professional	Contractor	Special	Premier	Professional	Special
	Ultimate Painters Tape	Superior Painters Tape	14 Day Masking Tape	Low Tack Painters Tape	7 Day Masking Tape	3 Day Masking Tape	Sensitive Painters Tape
							
Description	Rough & exterior masking	Precision masking	Multi purpose masking	Low Tack masking	General purpose masking	General purpose masking	Sensitive surfaces
Features:	Sharp Flats Lines	For Clean & crisp flat edges on most surfaces	For Clean & crisp flat edges on most surfaces	Clean, Sharp Flats Lines on delicate surfaces	Flat Edges	Flat Edges	Clean, Sharp Flats Lines on delicate surfaces
	High moisture / humidity resistance.	High moisture / humidity resistance.	High moisture / humidity resistance.	High moisture / humidity resistance.	Domestic DIY + Industrial painting	Domestic DIY + Industrial painting	High moisture / humidity resistance.
	Strong tear-resistant paper.	Strong tear-resistant paper.	Strong tear-resistant paper.	Strong tear-resistant paper.	High initial tack - Easy Tear	High initial tack - Easy Tear	Strong tear-resistant paper.
	Removes cleanly leaving no residue	Removes cleanly leaving no residue	Removes cleanly leaving no residue	Removes cleanly leaving no residue	Removes cleanly leaving no residue	Removes cleanly leaving no residue	Removes cleanly leaving no residue
Highly recommend for:	Irregular surfaces : Metals, tiles, untreated wood, Glass, PVC, Cured Painted surfaces	Most surfaces : Cured Painted Surfaces, Glass, PVC, Metal Tiles, Woods, Plastered Walls,	Most surfaces : Cured Painted Surfaces, Glass, PVC, Metal Tiles, Woods, Plastered Walls,	Delicate Areas : Wallpapers, Painted & Varnished Woods, etc..	Most surfaces : Cured Painted Surfaces, Glass, PVC, Metal Tiles, Woods, Plastered Walls,	Most surfaces : Cured Painted Surfaces, Glass, PVC, Metal Tiles, Woods, Plastered Walls,	Sensitive Areas : Freshly painted, Wallpapers, Plasterboards, plastered walls, etc..
Backing material:	Washi paper	Washi paper	crepe paper	Washi paper	crepe paper	crepe paper	Washi paper
Adhesive type:	Acrylic Adhesive	Acrylic Adhesive	Acrylic Adhesive	Acrylic Adhesive	Solvent-Based Natural Rubber	Solvent-Based Natural Rubber	Acrylic Adhesive
Width:	25-38-50	25-38-50	25-38-50	25-38-50	25-38-50	25-38-50	
True length:	50mtr	50mtr	50mtr	50mtr	50mtr	50mtr	
Thickness (micron):	0.09mm	0.09mm	0.16mm	0.10mm	0.12mm	0.12mm	0.07mm
Temperature Resistant	80°C Short Term	80°C Short Term	90°C for 45mins	100°C Short Term	80°C for 30mins 60°C for 60mins	60°C for 30mins	90°C Short Term
UV Resistant (days):	120 days	30 days	7 days	45 days	N/A	N/A	30 days
Can be left on for (days):	240 days	60 days	14 days	90 days	N/A	N/A	60 days
Release coating:	High	Medium	Medium	Low	Medium	Medium	Low
Colour (RAL):	Red	Gold	Blue	Purple	White	White	Violet
Adhesive strength:							
Adhesion to steel (N/10mm):	2.31	1.96		2.08	4.5	4	
Tensile (N / 15mm):	53.8	52.3	26	47.8	85	85	
Elongation (%):	7.7	2.6	20	3.9	9	8	



INDASOL Group

10 Crystal Drive, Sandwell Business Park, Smethwick B66 1QG

Tel: 0121 556 990 | Email: technical@indasol.co.uk | www.indasol.co.uk